

DIN-RAIL LIU 6 - 12 FIBER

As the name implies, the DIN Rail mount Compact LIU is made especially to attach on a common 35mm DIN rail. designed to be simple to operate in crowded areas, like an electrical panel. Its powder-coated metal housing, resistant to corrosive conditions, has a tremendous impact. The LIU features PG11 glands for a rapid and safe anchoring of the incoming wires, as well as convenient cable entrance from both the top and bottom. It also features a cable holder halfway as an extra anchor upon entering. It accepts both unarmoured and armored versions of single- and multimode cables. To secure the spliced pigtail(s) with the entering fiber core(s), the Splice Sleeve Holder(s) must be installed inside.

Features

- Compact Innovative Design •
- Robust Quality
- Superior Cable Management •
- Fiber Core Protection
- Maintains Fiber Bend Radius •
- DIN Rail Mount
- Single/Multimode Fiber
- Easy to Install & Maintain •
- Multi Cable Entry
- Multi-Adaptor Panels SC, LC, ST • 6
- core Expandable to 12-core
- International Standards Components



Technical Data :

- Fiber Capacity of panel : upto 12 Cores For
- SC | LC | FC 12 Fiber For SC PC/APC With
- Duplex Connectors Material : Cold Rolled Steel | 0.8mm Sheet Thickness Panel
- Connector : SC | LC
- Storage Temperature : -45~+65°C
- Splice tray with interconnect hinge design for upto 96 fibre management.
- Type : Double Door Wall Mount With Heavy
- Duty Lock Dimensions (in mm) 178* 130* 55

