

MEDIA CONVERTOR -SFP- 1 G

Product Description

BTON 10/100/1000M Media Converter SFP 1RJ45

Features

* Works at 100/1000Mbps in Full-Duplex mode for both TX port and FX port * Supports Auto MDI/MDIX for TX port * Provides switch configuration of Force /Auto transfer mode for FX port * FX port support hot-swappable * Extends -fiber distance up to 0.55/2km for multi-mode -fiber and 10/20/40/80/100/120km for single-mode -fiber * Easy-to-view LED indicators provide status to monitor network activity easily



SFP to Ethernet Converter

Order Information 950SFP-GE:10/100/1000M,1SFP+1RJ45

950SFP-FE:10/100M,1SFP+1RJ45

1SFP Slot and 1Ethernet port

10/100Mbps and 10/100/1000Mbps

For SFP 155Mbps or 1.25Gbps

Single Fiber/Dual Fiber 0~120km, LC connector

Optical Interface	Connector	SFP -LC
	Data Rate	100Mbps, 1000Mbps
	Duplex Mode	Full duplex
	Fiber	MM 50/125um,62.5/125um;SM 9/125um
	Distance	100Mbps: MM 2km,SM 25/40/60/80/100/120km

		1000Mbps: MM 550m/2km,SM 20/40/60/80km
	Wavelength	MM 850nm,1310nm SM 1310nm,1550nm WDM Tx1310/Rx1550nm(A side),Tx1550/Rx1310nm(B side) WDM Tx1490/Rx1550nm(A side),Tx1550/Rx1490nm(B side)
UTP Interface	Connector	RJ45
	Data Rate	10/100Mbps, 10/100/1000Mbps
	Duplex Mode	Half/full duplex
	Cable	Cat5,Cat6
Power Input	Adapter Type	DC5V
	Power Built-in Type	AC100~240V
	Power Consumption	<3W
Weight	Adapter Type	0.39kg
	Power Built-in Type	0.67kg
Dimension	Adapter Type	94*70*27cm
	Power Built-in Type	140.5*111*30cm
General	Temperature	0~50°C Operating; -40~70°C Storage
	Humidity	5~95%(no condensing)
	MTBF	≥10.0000h
	Certification	CE, RoHS