

MINI LIU 6 - 12 FIBER

The LIU features PG11 glands for a rapid and safe anchoring of the incoming wires, as well as convenient cable entrance from back. It also features a cable holder halfway as an extra anchor upon entering. It accepts both unarmoured and armored versions of single- and multimode cables. To secure the spliced pigtail(s) with the entering fiber core(s), the Splice Sleeve Holder(s) must be installed inside.

Features

- Compact Innovative Design
- Robust Quality
- Superior Cable Management
- Fiber Core Protection
- Maintains Fiber Bend Radius
- DIN Rail Mount
- Single/Multimode Fiber
- Easy to Install & Maintain
- Multi Cable Entry
- Multi-Adaptor Panels SC, LC, ST
- 6 core Expandable to 12-core
- International Standards Components



Technical Data :

- Fiber Capacity of panel : upto 12 Cores For SC | LC | FC
- 12 Fiber For SC PC/APC With Duplex Connectors
- Material : Cold Rolled Steel | 0.8mm Sheet Thickness
- Panel Connector : SC | LC
- Storage Temperature : -45~+65°C
- Splice tray with interconnect hinge design for upto 96 fibre management.
- Type : Double Door Wall Mount With Heavy Duty Lock
- Dimensions (in mm) 192* 128*42.6
- Weight : 600gm

